

E-W22



Intelligent multimedia performance, attractive slim design and hard glass durability: the E-W22 is tailor-made for any interactive professional environment.

The E-W22 features a brilliant 22" super-resolution widescreen that provides 28% more screen real estate than the typical 19" display. Capable of displaying two full-sized open windows, the E-W22 widescreen format allows for increased productivity. With the protection of NeoV™ Optical Glass, a convenient headphone jack, and built-in speakers for multimedia applications, the E-W22 is the utmost display for small office/home office environments or progressive classrooms, training centres and other multi-user spaces.

- > 22" widescreen format
- > WSXGA+ 1680 x 1050 resolution
- > NeoV™ Optical Glass
- > Slim modern exterior
- > Unique rear cover on backside of display
- > Swift 3 ms response time
- > Crisp 3000:1 dynamic contrast ratio
- > High 300 cd/m² brightness
- > Dual digital and analogue inputs
- > Built-in HDCP for HD-format video
- > 1080p support
- > Built-in speakers with headphone jack
- > Auto-adjustment for optimal settings
- > Hot key for preferred video mode: User, Text, Movie, Game, and Graphic
- > Kensington® security socket
- > VESA standard wall mount
- > Fold away base for quick storage



NeoV™ Optical Glass - The most trusted hard glass protection available. Only on AG Neovo displays

E-W22

Specifications		E-W22
Panel	Panel Type	TFT LCD
	Panel Size	22.0" (559 mm)
	Max. Resolution	WSXGA+ 1680 x 1050
	Pixel Pitch	0.282 mm
	Brightness	300 cd/m ² (Typical)
	Contrast Ratio	3000:1 (DCR)
	Viewing Angle (H/V)	170°/160° (Typical)
	Display Colour Response Time	16.7M 3 ms (GTG)
Frequency (H/V)		H: 30 kHz - 83 kHz V: 56 Hz - 75 Hza
Max. Pixel Clock	Analog	190 MHz
	Digital	165 MHz
Input	Analogue	15-Pin D-Sub
	Digital	24-Pin DVI-D
Audio	Audio In	3.5 mm Audio Line-in
	Audio Out	3.5 mm Headphone Jack
	Speaker	2 W x 2
Power	AC-DC Adaptor	External
	Power	AC 100 - 240 V, 50 - 60 Hz
	Consumption	< 48 W (On) < 2 W (Stand-by) < 1 W (Off)
NeoV™ Optical Glass	Thickness	3.0 mm (0.12")
	Reflection Rate	< 1%
	Transmission Rate	> 96%
	Coating Hardness	> 9H
Plug & Play	VESA	DDC 2B, DDC/CI
Operating Conditions	Temperature	0 °C ~ 40 °C
	Humidity	10% ~ 90%
Storage Conditions	Temperature	-20 °C ~ 60 °C
	Humidity	5% ~ 95%
Mounting	VESA FPMPMI	Yes (100 mm)
Tilt	Tilt	+5° ~ +25°
Dimensions	Product (W x H x D)	512 x 416 x 196 mm (20.1" x 16.4" x 7.7")
	Packaging (W x H x D)	594 x 564 x 202 mm (23.4" x 22.2" x 8.0")
Weight	Product Weight	7.9 kg (17.4 lbs)
	Packaged Product Weight	9.0 kg (19.8 lbs)
Regulation Approval	Certifications & Compliance	UL/CUL, TUV/Baurt, CB, GOST-R, FCC, CE, BSMI, WEEE, RoHS, Vista/Premium, PAT, REACH
Accessories	Supplied	Quick Guide, CD ROM (user manual and drivers), audio cable, power adaptor, power cord, 15-Pin D-Sub cable, 24-Pin DVI-D cable



Impressive modern exterior and slim design



NeoV™ Optical Glass protects against scratches, impacts and other physical damage



DVI input, built-in speakers and easy access headphone jack for multimedia and interactive applications



VESA standard wall mount allows for secure mounting almost anywhere

